


Cam Type Sash Latch







2C

Cam Type Sash Lock

	Description	Material	Finish		
2D 2E-L	sash lock & keeper sash lock only	steel steel	zinc plated		E
2E-K	keeper only	steel	nickel plated		
	rs not included des ball bearing f	+ + +		0.197[5.00] 4) HOLES 64 [16.2] (4) PLACES (4) PLAC	
				REDUCT Single Point	L-handle Latch with Keepe
Part Nu	ımber Mat	erial	Finish	-	
D465	304	ISS	polished		
flexib 90° h incre comp	andle operation, ments batible with both ing doors Ø 219[5:58] FOR #10 OR (8) HOLES	45° cam ad	justment i outward	TOP VIEW 1.22[31.0] 1.73[44.0] CENT.	patent pending
flexib 90° h incre comp	ility andle operation, ments batible with both ing doors Ø,219[5:69] FOR #10 OR (8) HOLES 2.13[54:0] + .213[54:0] + .33[16:0] - 1.22 ⁺²⁴ [10. ⁺⁶⁰] R	45° cam ad inward and M5 screws	Iush assembly justment I outward I outward	.e TOP VIEW 1.22[31.0] 1.21[30.8] 2.0[50] REF. 2.0[50] REF. 1.22[31.0] 1.22[31.0] 1.21[30.8] 1.22[31.0]	