## **Continuous Hinges with Holes**





## 302/304SS - Hand Polished - Drilled Countersunk Holes

Part Number	Material Thickness	Open Width	Pin Diameter	Knuckle Length	Hole Size	Length	Notes
MSS410	.040	1.06	.091	.50	<ul> <li>Ø.181 hole countersunk for a #5 F.H.S.</li> <li>Ø.211 hole countersunk for a #6 F.H.S.</li> <li>Ø.181 hole countersunk for a #6 F.H.S.</li> </ul>	72.00	<ul> <li>&gt; 302/304SS leaves and pin</li> <li>&gt; pin securely staked in place</li> <li>&gt; deeply drilled countersunk holes on 2.00" centers</li> <li>&gt; top side and knuckle polished to a high luster</li> <li>&gt; packaged to prevent scratching in transit</li> </ul>
MSS412	.040	1.25	.091	.50			
MSS415	.040	1.50	.091	.50			
MSS420	.040	2.00	.091	.50			
MSS615	.060	1.50	.120	.50			
MSS620	.060	2.00	.120	.50			

## 302/304SS - Mill - Drilled Countersunk Holes

Part Number	Material Thickness	Open Width	Pin Diameter	Knuckle Length	Hole Size	Length	Notes
MSS410M <b>‡</b>	.040	1.06	.091	.50	<ul><li>Ø.181 hole countersunk for a #5 F.H.S</li><li>Ø.211 hole countersunk for a #6 F.H.S.</li></ul>	72.00	<ul> <li>all details as above, except these hinges are mill finish (not polished or degreased).</li> <li>these hinges are non-stock</li> </ul>
MSS412M <b>‡</b>	.040	1.25	.091	.50			
MSS415M <b>‡</b>	.040	1.50	.091	.50			
MSS420M <b>‡</b>	.040	2.00	.091	.50			
MSS615M <b>‡</b>	.060	1.50	.120	.50	Ø.181 hole countersunk for a #6 F.H.S.		
MSS620M <b>‡</b>	.060	2.00	.120	.50			
MSS630M <b>‡</b>	.060	3.00	.120	.50			



## Premium Finish Steel Continuous Hinges with Countersunk Holes

	Part N Open	Screw Size	Finish		
1.06"	1.25"	1.50"	2.00"	Size	
NPSL41094	NPSL41294	NPSL41594	NPSL42094 <b>‡</b>	#4	NICKEL PREMIUM GRADE
	NPSL41295	NPSL41595	NPSL42095	#5	<ul> <li>top side high luster</li> <li>bottom side dull</li> </ul>
		NPSL41596	NPSL42096		<ul> <li>both sides lacquered</li> </ul>

- ► leaf thickness .040", pre-plated cold rolled steel
- ▶ stock lengths shown are 72.00" long
- pin diameter .091", galvanized pin staked in place
- coined countersunk holes on 2.00" centers for flat head screws

knuckle length .50"

‡ these hinges are non-stock