

## Component Parts

## Trim Ring

Part Number	Material	Outside Dia.	Height	Finish
<b>KH02NP</b>	steel	1.13 [28.6]	.087 [2.21]	nickel plated
<b>KH02CP</b>	steel	1.13 [28.6]	.087 [2.21]	chrome plated
<b>KH02BP</b>	steel	1.13 [28.6]	.087 [2.21]	brass plated
<b>KH02SS</b>	304SS	1.13 [28.6]	.087 [2.21]	tumbled & polished

- ▶ fits behind head of standard 3/4 [19] diameter lock



## Mounting Clip

Part Number	Material	Finish
<b>KH20</b>	spring steel	nickel plated

- ▶ holds lock in place instead of a hex nut for quicker installation
- ▶ for standard cam locks



## Washer

Part Number	Material	Outside Dia.	Thickness	Finish
<b>KH04</b>	steel	1.05 [26.6]	.031 [.79]	zinc plated

- ▶ fits standard 3/4 [19] diameter lock with two flats



## Mounting Clip

Part Number	Material	Finish
<b>KH23</b>	spring steel	zinc plated

- ▶ holds lock in place instead of a hex nut for quicker installation
- ▶ for standard cam locks
- ▶ low profile



## Stainless Steel 4-Prong Spur Washer

Part Number	Material	Outside Dia.	Thickness	Finish
<b>KH31SS</b>	304SS	1.00 [25.4]	.051 [1.19]	mill

- ▶ fits standard 3/4 [19] diameter lock with two flats
- ▶ recommended for wood applications



## 90° Reversible Stop Washer

Part Number	Finish
<b>KH40</b>	zinc plated

- ▶ reverses for clockwise or counterclockwise operation



## 4-Prong Spur Washer

Part Number	Material	Outside Dia.	Thickness	Finish
<b>KH32</b>	steel	1.31 [33.3]	.03 [ .79]	clear zinc

- ▶ fits standard 3/4 [19] diameter lock with two flats
- ▶ recommended for wood applications



## 180° Reversible Stop Washer

Part Number	Finish
<b>KH42</b>	zinc plated

- ▶ reverses for clockwise or counterclockwise operation



## Body Nuts

Part Number	Wrench Size	Thickness	Finish
<b>KH10</b>	.88 [22.2]	.172 [4.37]	nickel plated
<b>KH11</b>	1.00 [25.4]	.359 [9.13]	nickel plated
<b>KH12</b>	.88 [22.2]	.141 [3.57]	zinc plated

- ▶ material: die cast zinc
- ▶ fits standard 3/4 [19] diameter locks
- ▶ 3/4" - 24 thread



## Cam Mounting Screw

Part Number	Finish
<b>KH50</b>	zinc plated

- ▶ for locks with screw-on cam
- ▶ 1/4-20 UNC thread
- ▶ .23 [6.0] long
- ▶ Phillips head

